
REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average I hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT D		2. REPORT T Viewgraphs		3. DATES COV	
4. TITLE AND	SUBTITLE	1		5a. CONTRACT	T NUMBER
Ultrasonic Ima	ging of TTCP Sam	ples		5b. GRANT NUMBER 5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S	)		;	5d. PROJECT N	IUMBER
William R. Davis				5e. TASK NUM	BER
				5f. WORK UNI	T NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER	
Naval Air Warfare Center Aircraft Division 22347 Cedar Point Road, Unit #6 Patuxent River, Maryland 20670-1161					
9. SPONSORING/MONITORING AGENCY NAME(S) ANI ADDRESS(ES)			S(S) AND	10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/	MONITOR'S REPORT NUMBER(S)
12. DISTRIBUTION/AVAILABILITY STATEMENT					
Approved for public release; distribution is unlimited.  13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON William R. Davis
a. REPORT	b. ABSTRACT	c. THIS PAGE	or abblidge	0.111020	19b. TELEPHONE NUMBER (include area code)
Unclassified	Unclassified	Unclassified	SAR	15	(301) 342-3761

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18







# The Technical Cooperation Program (TTCP)

Technical Panel Annual Meeting

Materials Group TP-5


Evaluation of Samples Using Ultrasound Imaging Dr. Ignacio Perez William R. Davis

16 - 20 October 2000





RAH66 Quill Detector Face Drive Shaft (top), Quill Shaft (bottom left), small brace (bottom center), and flex beam (bottom right)








# RAH 66 Quill Shaft 7/8" thick by 6" dia. By 1 1/8" high ring.








1/8" high ring. A 1 MHz 1.5" diameter transducer was RAH 66 Quill Shaft is a 7/8" thick by 6" diameter by 1 used in through transmission mode. This shows a full height disbond 1/2" wide.










transmission. Thickness is 1/2 inch to 1 inch. Height 12.5 inch, RAH66 Quill Detector Face (Dr) Shaft Examined by through 5 3/4 inch diameter








#### Quill Detector Face Bottom section -heavy thickness section examined by through transmission at 2.25 MHz











RAH66 Quill Detector Face (Dr) Shaft imaged using a 2.5 MHz 1.5" diameter transducer in through transmission. The thin Top Section is approximately 0.625 inch thick.










## The RAH66 Flex beam, 1.125" thick x 5.25" x 2.375"




A STATE OF THE STA


Standard Control of the Control of t





### RAH66 Flexbeam imaged using Through Transmission at 2.25 MHz shows a darker line of marceling near the top











RAH66 Flex beam in tank. One sided imaging of the ultrasound by refection shows some near surface discontinuities near the end of the flex beam.








### IAMT prepreg box, overhead and side views











IAMT prepreg box imaged in through transmission using 5 MHz for high resolution







tank. Back reflection imaging of the bottom of the part shows IAMT prepreg box imaged using the reflection camera in the a discontinuity on one corner, and a surface discontinuity














IAMT prepreg box imaged by reflection in the tank. Back reflection imaging with an increased time delay shows the triangular machined area and the 4 ribs







using 5 MHz ultrasonic reflection camera in reflection 3 cm thick balsa wood cored multilayer panel imaged

